

TURVIP-2MP-HD-FG-S2

2MP HD ANALOGUE IR FIXED TURRET



White model also available
[substitute FG for FW in code]

- 2MP real-time image
- AHD / TVI / CVI / CVBS standard and lossless video output
- Up to 1000 TVL resolution
- High speed, long distance and real time transmission
- Auto colour to B/W at low illumination
- Supports ICR switch, true day / night
- Supports noise reduction
- Up to 30m IR night view distance
- IP67 ingress protection

Specification	TURVIP-2MP-HD-FG-S2
Camera	
Image Sensor	1 / 3 "CMOS
Resolution	2MP
Image Size	1920 x 1080
Video Output	AHD / TVI / CVI / CVBS
Image System	PAL / NTSC
Electronic Shutter	Auto; 1 / 50s ~ 1 / 100000s (PAL); 1 / 60s ~ 1 / 100000s (NTSC)
IR Distance	Up to 30m
Pan & Tilt	Pan: 0°~360°; Tilt: 0°~75°; Rotation: 0°~360°
Frame Rate	30fps (60Hz) / 25fps (50Hz)
Min. Illumination	0 lux (IR ON)
Lens	2.8mm fixed
Lens Mount	M12
S/N Ratio	≥52dB (AGC OFF)
Ingress Protection	IP67
Functions	
Function Control	OSD (COC Control)
Day & Night	ICR
Digital WDR	Yes
Digital DDR	Yes (2D/3D DNR)
AGC	Yes
Auto White Balance	Yes
BLC	Yes
Front Light Compensation	Yes
Sharpness	Yes
Smart IR	Yes
Image Setting	Yes
Defect Correction	Auto
Others	
Power Supply	DC12V (± 10%)
Power Consumption	IR OFF : < 1W; IR ON : < 3W
Working Environment	- 30 °C ~ 50 °C, 10 % ~ 90 % (relative humidity)
Dimensions (mm)	Φ 94.6 x 82.8
Weight (net)	Approx. 0.39KG